

```

*****
*
*          STAAD.Pro          *
*          Version 2007   Build 04   *
*          Proprietary Program of   *
*          Research Engineers, Intl. *
*          Date=   JUL 24, 2013   *
*          Time=   18:25:34   *
*
*          USER ID: Hewlett-Packard *
*****
    
```

```

1. STAAD SPACE
INPUT FILE: Structure1-Square.STD
2. START JOB INFORMATION
3. ENGINEER DATE 19-JUL-13
4. END JOB INFORMATION
5. INPUT WIDTH 79
6. UNIT INCHES POUND
7. JOINT COORDINATES
8. 1 0 0 0
9. 2 0 100 0
10. 3 100 100 0
11. 4 100 0 0
12. MEMBER INCIDENCES
13. 1      1      2
14. 2      2      3
15. 3      3      4
16. DEFINE MATERIAL START
17. ISOTROPIC STEEL
18. E 2.9E+007
19. POISSON 0.3
20. DENSITY 0.283
21. ALPHA 6.5E-006
22. DAMP 0.03
23. END DEFINE MATERIAL
24. MEMBER PROPERTY
25. 1 TO 3 PRIS YD 5 ZD 5
26. CONSTANTS
27. MATERIAL STEEL ALL
28. SUPPORTS
29. 1 4 FIXED
30. LOAD 1 LOADTYPE LIVE   TITLE LOAD CASE 1
31. JOINT LOAD
32. 3 FX 500
33. PERFORM ANALYSIS
    
```

P R O B L E M S T A T I S T I C S

NUMBER OF JOINTS/MEMBER+ELEMENTS/SUPPORTS = 4/ 3/ 2

SOLVER USED IS THE OUT-OF-CORE BASIC SOLVER

ORIGINAL/FINAL BAND-WIDTH= 1/ 1/ 12 DOF
TOTAL PRIMARY LOAD CASES = 1, TOTAL DEGREES OF FREEDOM = 12
SIZE OF STIFFNESS MATRIX = 1 DOUBLE KILO-WORDS
REQD/AVAIL. DISK SPACE = 12.0/ 231091.0 MB

34. PRINT ALL

JOINT COORDINATES

COORDINATES ARE INCH UNIT

JOINT	X	Y	Z
1	0.000	0.000	0.000
2	0.000	100.000	0.000
3	100.000	100.000	0.000
4	100.000	0.000	0.000

MEMBER INFORMATION

MEMBER	START JOINT	END JOINT	LENGTH (INCH)	BETA (DEG)	RELEASES
1	1	2	100.000	0.00	
2	2	3	100.000	0.00	
3	3	4	100.000	0.00	

STAAD SPACE

-- PAGE NO. 5

MATERIAL PROPERTIES.

ALL UNITS ARE - POUN INCH

MATERIAL

	KIND	E	POIS	DENS	ALPHA	DAMP	G
STEEL	1D	2.90000E+07	0.300	2.83000E-01	6.50000E-06	0.030	1.11538E+07

MATERIAL PROPERTIES.-----
ALL UNITS ARE - POUN INCH

MEMBER	E	G	DEN	ALPHA
1	29000000.0	11153846.0	0.28299999	0.00000650
2	29000000.0	11153846.0	0.28299999	0.00000650
3	29000000.0	11153846.0	0.28299999	0.00000650

MEMBER PROPERTIES. UNIT - INCH

MEMB	PROFILE	AX/ AY	IZ/ AZ	IY/ SZ	IX/ SY
1	PRISMATIC	25.00 21.25	52.08 21.25	52.08 20.83	88.02 20.83
2	PRISMATIC	25.00 21.25	52.08 21.25	52.08 20.83	88.02 20.83
3	PRISMATIC	25.00 21.25	52.08 21.25	52.08 20.83	88.02 20.83

SUPPORT INFORMATION (1=FIXED, 0=RELEASED)

UNITS FOR SPRING CONSTANTS ARE POUN INCH DEGREES

JOINT	FORCE-X/ KFX	FORCE-Y/ KFY	FORCE-Z/ KFZ	MOM-X/ KMX	MOM-Y/ KMY	MOM-Z/ KMZ
1	1 0.0000E+00	1 0.0000E+00	1 0.0000E+00	1 0.000E+00	1 0.000E+00	1 0.000E+00
4	1 0.0000E+00	1 0.0000E+00	1 0.0000E+00	1 0.000E+00	1 0.000E+00	1 0.000E+00

***** END OF DATA FROM INTERNAL STORAGE *****

35. PRINT JOINT DISPLACEMENTS ALL

JOINT DISPLACEMENT (INCH RADIANS) STRUCTURE TYPE = SPACE

JOINT	LOAD	X-TRANS	Y-TRANS	Z-TRANS	X-ROTAN	Y-ROTAN	Z-ROTAN
1	1	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000
2	1	0.01986	0.00003	0.00000	0.00000	0.00000	-0.00012
3	1	0.01989	-0.00003	0.00000	0.00000	0.00000	-0.00012
4	1	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000

***** END OF LATEST ANALYSIS RESULT *****

36. LOAD LIST ALL

37. PRINT MEMBER FORCES ALL

MEMBER END FORCES STRUCTURE TYPE = SPACE

ALL UNITS ARE -- POUN INCH (LOCAL)

MEMBER	LOAD	JT	AXIAL	SHEAR-Y	SHEAR-Z	TORSION	MOM-Y	MOM-Z
1	1	1	-213.90	249.84	0.00	0.00	0.00	14294.67
		2	213.90	-249.84	0.00	0.00	0.00	10689.78
2	1	2	-249.84	-213.90	0.00	0.00	0.00	-10689.78
		3	249.84	213.90	0.00	0.00	0.00	-10700.15
3	1	3	213.90	250.16	0.00	0.00	0.00	10700.15
		4	-213.90	-250.16	0.00	0.00	0.00	14315.41

***** END OF LATEST ANALYSIS RESULT *****

38. PRINT MEMBER FORCES GLOBAL ALL

STAAD SPACE

-- PAGE NO. 10

MEMBER END FORCES STRUCTURE TYPE = SPACE

ALL UNITS ARE -- POUN INCH (GLOBAL)

MEMBER	LOAD	JT	FX	FY	FZ	MX	MY	MZ
1	1	1	-249.84	-213.90	0.00	0.00	0.00	14294.67
		2	249.84	213.90	0.00	0.00	0.00	10689.78
2	1	2	-249.84	-213.90	0.00	0.00	0.00	-10689.78
		3	249.84	213.90	0.00	0.00	0.00	-10700.15
3	1	3	250.16	-213.90	0.00	0.00	0.00	10700.15
		4	-250.16	213.90	0.00	0.00	0.00	14315.41

***** END OF LATEST ANALYSIS RESULT *****

39. PRINT MEMBER STRESSES ALL

MEMBER STRESSES

ALL UNITS ARE POUN/SQ INCH

MEMB	LD	SECT	AXIAL	BEND-Y	BEND-Z	COMBINED	SHEAR-Y	SHEAR-Z
1	1	.0	8.6 T	0.0	686.1	694.7	15.0	0.0
		1.00	8.6 T	0.0	513.1	521.7	15.0	0.0
2	1	.0	10.0 T	0.0	513.1	523.1	12.8	0.0
		1.00	10.0 T	0.0	513.6	523.6	12.8	0.0
3	1	.0	8.6 C	0.0	513.6	522.2	15.0	0.0
		1.00	8.6 C	0.0	687.1	695.7	15.0	0.0

***** END OF LATEST ANALYSIS RESULT *****

40. PRINT SUPPORT REACTION ALL

STAAD SPACE

-- PAGE NO. 12

SUPPORT REACTIONS -UNIT POUN INCH STRUCTURE TYPE = SPACE

JOINT	LOAD	FORCE-X	FORCE-Y	FORCE-Z	MOM-X	MOM-Y	MOM Z
1	1	-249.84	-213.90	0.00	0.00	0.00	14294.67
4	1	-250.16	213.90	0.00	0.00	0.00	14315.41

***** END OF LATEST ANALYSIS RESULT *****

41. FINISH

***** END OF THE STAAD.Pro RUN *****

**** DATE= JUL 24,2013 TIME= 18:25:34 ****

```

*****
*           For questions on STAAD.Pro, please contact           *
*   Research Engineers Offices at the following locations         *
*                                                                 *
*           Telephone                                           Email           *
*   USA:      +1 (714)974-2500      support@bentley.com      *
*   CANADA    +1 (905)632-4771      detech@odandetech.com     *
*   UK        +44(1454)207-000      support@bentley.com      *
*   NORWAY    +47 67 57 21 30      staad@edr.no             *
*   SINGAPORE +65 6225-6158        support@bentley.com      *
*   INDIA     +91(033)4006-2021     support@bentley.com      *
*   JAPAN     +81(03)5952-6500      eng-eye@crc.co.jp        *
*   CHINA     +86(411)8479-1166     support@bentley.com      *
*   THAILAND  +66(0)2645-1018/19    support@bentley.com      *
*                                                                 *
*   North America      support@bentley.com      *
*   Europe              support@bentley.com      *
*   Asia                support@bentley.com      *
*****

```

